

## TC SMART



## Overview

With its new TC7 SMART heat press, Secabo opens up new innovative paths leading to even better performance. This latest development of the successful automatic knee-lever press Secabo TC7 introduces a world novelty to the market, which opens up a variety of new options to users: The controller of the TC7 SMART now comes equipped with a Bluetooth interface that allows for controlling the press via the free app Secabo Smart Transfer, while also providing access to a comprehensive function database. This allows users to: Simply enter the type of fabric and the transfer material and immediately retrieve the matching combinations of temperature, time and pressure. Additional features, such as the calculation of heat-up times and warning functions, make the app a valuable assistant for all common heat transfer methods. The new heat press Secabo TC7 SMART offers a work surface of 40 x 50 cm, is easy to use and robust in ongoing operation. The modular design allows for quick and easy installation of removable plates in various formats, a quick change system and a slide extension.

## Features



### Secabo Smart Transfer App

The device is ready for control via the Secabo app. With the aid of this app, suitable transfer parameters can be selected for your application.



### Bluetooth interface

The device can be connected and controlled via Bluetooth with a mobile device and the Secabo Smart Transfer App.



### Digital controller

Duration and temperature can easily be adjusted and monitored using the digital controller.



### Large workspace

Due to the large folding angle of 40°, the transfer objects can be aligned comfortably and precisely.



### Low hysteresis

A state-of-the-art controller reduces the temperature fluctuations to a minimum, thus ensuring consistently good transfer results.



### Variable work pressure

The work pressure is easy to adjust – in each case matching the transfer object and procedure.



### Opens automatically

The heat press automatically opens after the set time has elapsed.



### Safe working

The safety and quality of this device is constantly monitored – according to German safety standards.



### Precise temperature distribution

The high-quality heat plate ensures an exact temperature distribution over the entire heating surface.



### Replaceable plates

Interchangeable base plates available – also in combination with a quick-change system

## Technical Data

Dimensions open	43cm x 93cm x 74cm
Dimensions closed	43cm x 57cm x 75cm
working area	40cm x 50cm
scope of delivery	Mechanical base, heating plate and base plate, controller box, C13 power supply cable, tools, operating instructions
pressure setting	the heating plate can be adjusted with a hand reel
max. downforce	250 g / cm <sup>2</sup> g
max temperature	225 °C °C
maximum time preset	999 s s
max. clam angle	40 ° °
power supply	AC voltage 230V / 50Hz - 60Hz, 2.0kW
environment	+5°C - +35°C / 30% - 70% humidity
weight without packaging	39,00 kg
weight with package	45,00 kg
Brand	Secabo

## Views

