

POLI-FLEX® DIMENSION

Product Information

Casted, plotter cuttable polyurethane film with high-quality matt surface finish. Due to the thickness of 600 μ optical attractive 3D-transfers are resulting.

POLI-FLEX DIMENSION is suitable to transfer onto textiles like cotton, mixtures of polyester/cotton and polyester/acrylic. POLI-FLEX DIMENSION can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

POLI-FLEX DIMENSION can be cut with all current plotters. We recommend using a standard 60° knife. After weeding the cut flex film is transferred by heat press. The PET liner should be removed warm. Nylon and textiles with hydrophobic impregnation are not suitable for heat transfer. In this case we recommend using POLI-FLEX NYLON.

POLI-FLEX DIMENSION excels due to an excellent opacity.

The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals. Guarantee for a secure and long-lasting bond of POLI-FLEX DIMENSION is only given when following the specified temperature and pressure conditions.

We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

Technical Data

Transfer Film: Polyurethane, cast

Adhesive: Polyurethane-hotmelt

Thickness [mm] 0,60

Liner: PET-film, non adhesive

Transfer Conditions

Temperatur: 160 °C

Pressure: 3,0 bar [medium pressure]

Time: 25 sec.

Wash Resistance

Wash resistance: 60 °C

Wash textiles inside out.

Standard Dimensions

500 mm x 10 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17 53424 Remagen – GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37

E-Mail: info@poli-tape.de www.poli-tape.de

30/03/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.