



MIURA PLUS

AUTOMATIC XY CUTTER WITH VERTICAL ALIGNMENT

High performing cutting machine for X and Y trimming of flexible materials
with automatic vertical cutting correction.

- > Combined horizontal and vertical cutting for the fastest finish for your printed and unprinted rolls
- > Extremely high precision is ensured thanks to the automatic **EDGE CONTROL** that reads either the line longitudinally printed or the material's edge along the entire length of the roll
- > High performing trimmer: cut one roll of 50 meters (164 ft) in 3 minutes
- > 3 operation modes: crop mark, custom (sheeting) and manual. Miura can trim different lengths from the same printed roll
- > Intuitive set up parameters thanks to the user-friendly software (LCD touch screen display). New **MUTING** function to avoid misreading of hidden marks on the printed media


SUITABLE FOR:

- ☒ Paper (also laminated or encapsulated)
- ☒ Wallpaper
- ☒ Vinyl & self adhesive vinyl
- ☒ Backlit & frontlit display
- ☒ Reflective material
- ☒ PVC banner (up to 900 gr/m² - 27 oz./ya²)
- ☒ Magnetic rubber
- ☒ Polycarbonate (film)
- ☒ Canvas & polyester (with liner)
- ☒ Many more..





Automatic vertical alignment control panel




Optical sensor for vertical alignment



Advanced cutting mark reader



User-friendly software design



Fine positioning of the cutting blades (optional)




Fine pressure adjustment (according to the types of material)



NEW



- Can be fitted with:
1. Adjustable collecting table (optional)
 2. **NEW** Motorized Stacker in line with the cutter: height and inclination electronically adjustable; extensible length up to 3,1 meters (optional)



NEW

Slimline lengthwise rotary crush cutter, single or twin, (optional)



Single lengthwise rotary crush cutter (twin cutters optional)

	MIURA 160 PLUS	MIURA 265 PLUS
Working width	1650 mm (65 in)	2650 mm (105 in)
Maximum cutting thickness	1,2 mm (0,04 in)	1,2 mm (0,04 in)
Feeding speed	1 - 30 m/min. (3 - 98 ft/min)	1 - 30 m/min. (3 - 98 ft/min)
Usable cutting units	max. 8	max. 8
Cross cutting speed	5 - 120 m/min (16 - 393 ft/min)	5 - 120 m/min (16 - 393 ft/min)
Max. roll diameter	300 mm (12 in)	300 mm (12 in)
Max. roll weight	60 kg (132 lbs)	60 kg (132 lbs)
Power supply	230 V - 50 Hz - 650 W	230 V - 50 Hz - 650 W
Dimensions (W x D x H)	2400 x 1200 x 1350 mm (94 x 47 x 53 in)	3500 x 1200 x 1350 mm (137 x 47 x 53 in)
Weight	340 kg (749 lbs)	510 kg (1124 lbs)
Packing dimensions (W x D x H)	2650 x 1300 x 1400 mm (104 x 51 x 55 in)	2750 x 1300 x 1400 mm (108 x 51 x 55 in)
Packing weight	425 kg (936 lbs)	595 kg (1312 lbs)

Distributor

Manufactured in compliance with CE regulations



Follow us:



100 % Made by FLEXA
100 % Made in Italy

