



# PrintTex®




## Artist Mambo

Fields of application

**.02 .04 .05 .07**

### Specifications

-  **REF.** 564160 237
-  100 % polyester
-  ca. 160/ 252/ 320/ 505 cm  
ca. 63/ 99/ 126/ 199 inch  
other widths available on request
-  B-s1, d0    DIN EN 13501-1
-  ca. 170 g/m<sup>2</sup>  
ca. 5.0 oz/yd<sup>2</sup>
-  ca. 0.30 mm  
ca. 300 µm
-  rolls  
50/ 100 m  
55/ 109 yd
-  **Light**  
blank: 28.1 %  
DIN EN 410
-  **UV**  
blank: 3.9 %  
DIN EN 410
-  coated side: 7-8  
uncoated side: 6  
DIN EN ISO 105-B02
-  blank: 96.35  
DIN 5033-1
-  cold, heat, ultrasonic cut

-  warp: 1317 N  
weft: 1353 N  
DIN EN ISO 13934-1
-  warp: 31.3 %  
weft: 31.6 %  
DIN EN ISO 13934-1
-  warp: 0.8 %  
weft: 1.2 %  
DIN EN 14704-1

### Printing methods

print	UV	Latex	Dyesub
Inside	•	•	
Outside			•


### Certifications



## PrintTex® Artist Mambo

Fields of application

.02 .04 .05 .07



Ref.-Nr.: 564160 237 | Preview print sample