




PRODUCT REFERENCE

# GREY BACK

CHARACTERISTICS	BASE CLOTH	100% Polyester
	WIDTH AVAILABLE	61 inch / 122 inch / 200 inch 155 cm / 310 cm / 510 cm
	WEIGHT	4,87 oz. /sq. yd 165 g/m <sup>2</sup>
	THICKNESS	0,18 mm
	FIRE CLASSIFICATION	B1 in process
	TENSILE STRENGTH	Warp/Weft : 44 daN / 62 daN CH/TR : 44 daN / 62 daN
	PRINTING	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid gray; border-radius: 5px; padding: 5px; text-align: center;">  <p>DYE SUB TRANSFER</p> </div> <div style="border: 1px solid gray; border-radius: 5px; padding: 5px; text-align: center;">  <p>DYE SUB DIRECT</p> </div> <div style="border: 1px solid gray; border-radius: 5px; padding: 5px; text-align: center;">  <p>UV</p> </div> <div style="border: 1px solid gray; border-radius: 5px; padding: 5px; text-align: center;">  <p>LATEX</p> </div> <div style="border: 1px solid gray; border-radius: 5px; padding: 5px; text-align: center;">  <p>SOLVENT</p> </div> </div> <p>Printing with solvent, UV &amp; latex inks on the coated side</p>
	FIELD OF APPLICATION	Trade show booth / Fontlit display in frame system
	CERTIFICATION	

EDITION : 26/07/2017 / REF : DECOPRINT\_FT\_GREY BACK / CONCEPTION ET REALISATION : SERVICE COMMUNICATION SENFA

All details are nominal values and are subject to change within usual tolerance (+/- 10 %). The information provided in this document is based on current knowledge and expertise. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor.