

# DirectTex<sup>®</sup> Spinnaker Economy

Fields of application

**.02 .04 .06 .07**

## Specifications



501065 119



100 % polyester  
weave fabrics  
PVC-free, recyclable



ca. 155/ 310 /505 cm  
ca. 61/ 122/ 199 inch  
other widths available on request



B-s1, d0    DIN EN 13501-1  
M1            NF P 92 503 - 507



ca. 65 g/m<sup>2</sup>  
ca. 1.9 oz/yd<sup>2</sup>



ca. 0.13 mm  
ca. 130 μm



rolls  
50/ 100 m  
55/ 109 yd



blank:    5  
DIN EN ISO 105-B02



100 Pa:    73 l/(m<sup>2</sup>s)  
200 Pa:    125 l/(m<sup>2</sup>s)  
DIN EN ISO 9237



length:    582 N (18.5 N)  
cross:      652 N (21.7 N)  
DIN EN ISO 13934-1 (13937-2)



length:    25.0 %  
cross:      33.1 %  
DIN EN ISO 13934-1



UV stable



heat, ultrasonic cut


## Printing methods

print	UV	Latex	Dyesub
Inside	•	•	•
Outside	•	•	•

## Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	1,7 %	2,6 %	•
190°C	1,3 %	3,3 %	
200°C	1,3 %	4,8 %	
210°C	1,4 %	6,5 %	

## Certifications



## DirectTex® Spinnaker Economy

Fields of application

**.02 .04 .06 .07**



Ref.-Nr.: 501065 119 | Preview print sample