

Product Information

POLI-MOUNT 385 is based on an UV-cross-linked, closed-cell polyethylene foam, laminated on both sides with a solvent acrylic adhesive. The adhesive offers an excellent resistance against ageing and temperature. The liner made by a siliconized polyethylene film (green) grants protection of the adhesive against all weather conditions.

Especially to be emphasised are the following properties:

- The high grade solvent acrylic adhesive offers a high initial tack which guarantees an easy mounting under industrial conditions. Mounting of displays, product samples, plates and screens.
- The adhesive experiences a major increase of adhesion within the first 48 hours, and will reach a firm and solid final adhesion even under the influence of high temperatures and humid conditions.
- The permanent elastic and compressible PE-foam carrier is suitable for rough and uneven surfaces which contribute to an increase of the final adhesion strength.

Technical Data

Carrier:	PE-foam	
Adhesive:	Acrylic	
Liner:	PE-film, green	
Adhesion [N/cm]:	4,20	+/- 10 %
Thickness [mm]:	1,00	+/- 5 %
Temperature resistance [°C]:	-40 / +80	

Standard Dimensions

1.500 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.