

Version: A0

NMEQS-1805

(Size) :

1、Isotropic magnet (barium)/low, 30M × 620 × 0.75mm/MUV/2.0mm Pole pitch/ Chinese adhesive

(Dimensions: & Tolerance) :

Item	Length (m)	Width (mm)	Thickness (mm)	Thickness of adhesive (mm)
Size	30	620	0.75	0.20
Tolerance	0/+0.6	-1/+3	±0.05	±0.02

(Pull Strength) :

Code	Thickness (mm)	Pole pitch (mm)	Pull (g/cm ²)
Isotropic magnet (barium)	0.75	2.0	≥30

Physical Data:

Total thickness (mm)	0.95 ± 0.07
Reference Weight (g/m ²)	2675 ± 268
Hardness (Shore D)	45 ± 5
Flexibility (Φ6mm)	Without cracking
Opacity	100%

Version: A0

NMEQS-1805

Storage:

Working Condition: The optimum temperature range is 21 °C--38°C. It's not recommended to apply while the initial temperature is lower than 10°C, because the adhesive is too hard to paste on the object completely. However, if it has been affixed properly, the sticking force of adhesive can keep in ideal state in the low temperature.

Storage Condition: 25° C and 50% humidity conditions

Shelf life: 12 months under original packaging condition

The magnetic force is permanent and will not degrade in normal temperature without strong magnetic interference.

Packing:



in carton



in pallet (quantity per pallet will be as actual)