

## **Product Information**

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1



# P.S. SUBLI LT

**Description** PU plotter cut heat seal material with adhesive polyester backing, specifically conceived for low temperature transfers on polyester textiles colored with sublimation inks.

> The special structure and processing of the material create a barrier to the dyes, preventing the "migration" effect and maintaining thus unaltered the original color.

Suitable for polyammide or polyester fabrics not treated.

- **Usage** Mirror cut the material
  - Weed the exceeding material
  - Place the material on the garment with its polyester backing
  - Heat apply at the conditions shown on the right
  - Remove the support warm or cold

Do not stack or fold the clothings warm in order to avoid staining of the external surface



### Transfer settings

Speed: 30 cm/sec

Average thickness

Suggested cutting

110 microns

settings

Blade: 45° Pressure: 60 gf

15 seconds 130°C (266°F) medium pressure (3-4 bar)

### Washing

Wait at least 24 hours from application before washing. Washing resistance up to 40°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

The product is REACH compliant The product is certified Öko-Tex® Standard 100 Class I The product is VEGANOK certified







Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience.

> We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

