

## COLORPRINT PU

### Description



PU heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent or eco solvent based inks.  
Average film thickness before application: **80 micron**

### Basic information

Due to the many different base materials available on the market, the following instructions are given as a guideline only :  
Plotter settings (eg. with ROLAND VP-300)

Blade: **new at 50°**

Minimum required pressure: **65 gf**

#### Transfer setup

Temperature: **155°C** (310°F)

Time: **15"**

Pressure: **medium (3÷4 bar)**

### Application instructions

Print and cut the material

Weed the exceeding material

Remove the print from the polyester backing using Siser's T.T.D. Easy (adhesive, transparent and resistant to high temperatures)

Heat apply

Remove the application tape warm (should you use other application tapes, follow the manufacturer's instructions)

### Suitable textiles

Cotton, polyester and blends of these materials  
(not suited for treated and dye sublimation fabrics)

### Washing instructions

Wait **24h** after the heat transfer

**60°C Max-** inside out

Do not use bleach or other aggressive chemical agents.

Dry clean: **no**

Tumble dry: **yes**



Siser s.r.l.

N.B.

All information given in this sheet are based on our experience.  
We always recommend performing a test before starting standard production.  
For best results we recommend to store the product away from direct sunlight.

Viale della Tecnica n° 18  
36100 Vicenza - Italy  
Tel. +39 0444.287960  
Fax +39 0444.287959  
info@siser.it - www.siser.it

r.e.a. vi 171856 - reg. imp. vi n° 14971  
c.s. € 103.300 i.v. - p.iva 01591490246

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).  
This document can be subject to variations. Updated versions are available on our website www.siser.it.  
For further information, please contact our Sales Office.  
Thank you.