ProductData CL*Media SPF LabelStock

DescriptionMaterial

- self-adhesive polyester film for colour laser copiers and printers

Properties - good toner adhesion

- resistance to scratches and bending

- weather-proof

Application - indoor and outdoor

Durability - short-term

Printing systems - black and white laser printers

black and white copierscolour laser printers

- colour copiers

Examples of UseIndoor and outdoor

 self-adhesive labels, stickers, signs, type plates, decorative labels on plates and boards made of plastic, glass, metal or any other lacquered

flat and smooth surfaces.

Surface Protection

SPF can be used outdoor without lamination. However, we recommend to protect its surface to improve weathering resistance or if the film is subject to mechanical influences. In this case you should use self-adhesive laminating foils. If silicon oil is added depending on the type of machine this may influence the adherence of the laminating foil on the film's surface. Make some tests on a sample sheet before further

processing.

Adhesing SPF will stick to any solid, smooth surfaces which are dry and

free of dirt, grease, oil, silicon etc. During glueing the

temperature should not be below 15°C.

Technical Data Base material PET film ~ 50 micron

Adhesive Dispersion

Tackiness ~ 3,5 - 5,0 N / 25mm (A.F.E.R.A)

Temperature range glued +5°C up to +80°C

Backing paper silicon paper
Paper weight ~ 100 g/m²
Total thickness ~ 155 micron

Dimensions sheets DIN A4 and DIN A3

Storage SPF should be stored in its original packing in a cool and dry

environment.

The information in this Data Sheet is based on our knowledge and experience to date. The Data Sheet describes products in the case of safety requirements. The data and information do not Represent any property guarantee.

The Magic Touch GmbH, Benzstrasse 17, 64807 Dieburg, Germany - www.themagictouch.com