

Description

This double-sided tape consists of a white polyethylene foam coated on both sides with a modified acrylic adhesive. The adhesive has high initial adhesion even on rough and difficult substrates.

Carrier

Closed-cell polyethylene foam (2000 micron, white)

Liner

Double-sided siliconised paper (90 g/m², blue)

Adhesive

Modified acrylic

Area of use

This adhesive is suitable for the commercial assembly of extruded and injection-moulded plastic parts such as screens, strips, cable ducts and Plexiglas mirrors for interior and display applications. It is used for bonding hooks, signs, holders and dispensers as well as for exhibition and shop construction. Due to its high resistance to UV, water and aging, this product is suitable for outdoor applications.

Technical Data

Thickness* (foam and adhesive)	2100 micron	
Density*	58 kg/m ³	
Temperature resistance***	-40° C to +100° C	
Loop Tack* (FINAT TM 9)	28 N/25 mm	
Adhesion* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	18 N/25 mm
	after 20 min	> 19 N/25 mm, foam tear
	after 24 h	> 19 N/25 mm, foam tear
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 300 hours	at 23° C
	> 3 hours	at 70° C
Temperature resistance* (S.A.F.T.)	85° C	
Shelf life**	2 years	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

Available liner versions

- 09 Double-sided siliconised paper (90 g/m², white)
- K3 Double-sided siliconised polypropylene (100 micron, yellow)
- TM Double-sided siliconised paper (90 g/m², white with blue ORAFOL logo)

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.