

Product Information

Double-sided Polyester adhesive tape coated with an acrylic adhesive of a high tack level.

Beside an excellent ageing, weather and UV-resistance POLI-FIX 343 offers a well specific adhesion for mounting of unpolar plastic such as Polyethylene, Polypropylene and EPDM-rubber.

POLI-FIX 343 is suitable for a long term mounting for a huge variety of materials such as metal, plastics, wood, paper, glass or ceramics, for in- and outdoor use.

Especially to be emphasised are the following properties:

- Mounting of plastic profiles and for furniture.
- Self-adhesive equipment for rubber and EPDM-profiles.
- Mounting screens, holders and cable trunkings.
- Mounting of ABS parts in the automotive industry.

Technical Data

Carrier:	PET-film	
Adhesive:	Acrylic, modified	
Liner:	PP-film, red (80 g/m ²)	
Adhesion [N/cm]:	6,90	+/- 10 %
Thickness [mm]:	0,22	+/- 5 %
Temperature resistance [°C]:	-40 / +120	

Standard Dimensions

1.240 mm x 100 m

1.240 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.