

Slim Game Player

for medium & large channel letters

Specifications

Operating Temperature	30°C - +60°C
Storage Temperature	-30°C - +60°C
Body Material	Case: ABS Optics: Optical PC
Finishing	Ultrasonic Welding
Lead Wire	Tin Coated Copper Wire
Lifetime TM21	>60.000 Hours
Adhesive Tape	3M VHB™
Strip Size	50 Modules/Strip

 **ONE WHITE**
COLOR CONSISTENCY

 **50.000**
HOURS LIFETIME

Module Spacing: 175mm / 6.89"

2.80"
71MM



0.59"
15MM

IP67
PROTECTION

MADE IN
EUROPE

5 YEARS
WARRANTY

 **UL / CE**
CERTIFIED



Beam



Angle

Your OEM LED Module

MADE IN EUROPE

Visit next page to view product models

www.tmtleds.com



MADE IN
EUROPE

5 YEARS
WARRANTY



0.72W

Platinum

Constant Current | 3 SDCM

Power	Current	60W PS Loading		
0.72W	60mA	80 Total / 80 Single		
Order Code	Color	Lumen	Lm/W	
SPP12072-100A	10.000K	86	119	
SPP12072-065A	6.500K	86	119	
SPP12072-057A	5.700K	86	119	
SPP12072-050A	5.000K	86	119	
SPP12072-040A	4.000K	80	111	
SPP12072-030A	3.000K	80	111	
SPP12072-027A	2.700K	75	104	

1.08W

Platinum

Constant Current | 3 SDCM

Power	Current	60W PS Loading		
1.08W	90mA	55 Total / 55 Single		
Order Code	Color	Lumen	Lm/W	
SPP12108-100A	10.000K	127	118	
SPP12108-065A	6.500K	127	118	
SPP12108-057A	5.700K	127	118	
SPP12108-050A	5.000K	127	118	
SPP12108-040A	4.000K	118	109	
SPP12108-030A	3.000K	118	109	
SPP12108-027A	2.700K	106	98	

0.72W

Gold

Constant Voltage | 3 SDCM

Power	Current	60W PS Loading		
0.72W	60mA	80 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPG12072-100A	10.000K	86	119	
SPG12072-065A	6.500K	86	119	
SPG12072-057A	5.700K	86	119	
SPG12072-050A	5.000K	86	119	
SPG12072-040A	4.000K	80	111	
SPG12072-030A	3.000K	80	111	
SPG12072-027A	2.700K	75	104	

1.08W

Gold

Constant Voltage | 3 SDCM

Power	Current	60W PS Loading		
1.08W	90mA	55 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPG12108-100A	10.000K	127	118	
SPG12108-065A	6.500K	127	118	
SPG12108-057A	5.700K	127	118	
SPG12108-050A	5.000K	127	118	
SPG12108-040A	4.000K	118	109	
SPG12108-030A	3.000K	118	109	
SPG12108-027A	2.700K	106	98	

0.72W

Chrome

Constant Current | 5 SDCM

Power	Current	60W PS Loading		
0.72W	60mA	80 Total / 80 Single		
Order Code	Color	Lumen	Lm/W	
SPC12072-100A	10.000K	75	104	
SPC12072-065A	6.500K	75	104	
SPC12072-057A	5.700K	75	104	
SPC12072-050A	5.000K	75	104	
SPC12072-040A	4.000K	70	97	
SPC12072-030A	3.000K	70	97	
SPC12072-027A	2.700K	65	90	

1.08W

Chrome

Constant Current | 5 SDCM

Power	Current	60W PS Loading		
1.08W	90mA	55 Total / 55 Single		
Order Code	Color	Lumen	Lm/W	
SPC12108-100A	10.000K	110	102	
SPC12108-065A	6.500K	110	102	
SPC12108-057A	5.700K	110	102	
SPC12108-050A	5.000K	110	102	
SPC12108-040A	4.000K	102	94	
SPC12108-030A	3.000K	102	94	
SPC12108-027A	2.700K	95	88	

0.72W

Silver

Constant Voltage | 5 SDCM

Power	Current	60W PS Loading		
0.72W	60mA	80 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPS12072-100A	10.000K	75	104	
SPS12072-065A	6.500K	75	104	
SPS12072-057A	5.700K	75	104	
SPS12072-050A	5.000K	75	104	
SPS12072-040A	4.000K	70	97	
SPS12072-030A	3.000K	70	97	
SPS12072-027A	2.700K	65	90	

1.08W

Silver

Constant Voltage | 5 SDCM

Power	Current	60W PS Loading		
1.08W	90mA	55 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPPS12108-100A	10.000K	110	102	
SPPS12108-065A	6.500K	110	102	
SPPS12108-057A	5.700K	110	102	
SPPS12108-050A	5.000K	110	102	
SPPS12108-040A	4.000K	102	94	
SPPS12108-030A	3.000K	102	94	
SPPS12108-027A	2.700K	95	88	

Luminous flux tolerance ±10% - CCT tolerance ±8%

IP67
PROTECTION

MADE IN
EUROPE

5 YEARS
WARRANTY

UL / CE
CERTIFIED

1.20W Platinum

Constant Current | 3 SDCM

Power 1.20W	Current 100mA	60W PS Loading 50 Total / 50 Single		
Order Code	Color	Lumen	Lm/W	
SDPP12120-100A	10.000K	136	113	
SPP12120-065A	6.500K	136	113	
SPP12120-057A	5.700K	136	113	
SPP12120-050A	5.000K	136	113	
SPP12120-040A	4.000K	127	106	
SPP12120-030A	3.000K	127	106	
SPP12120-027A	2.700K	118	99	

1.50W Platinum

Constant Current | 3 SDCM

Power 1.50W	Current 125mA	60W PS Loading 40 Total / 40 Single		
Order Code	Color	Lumen	Lm/W	
SPP12150-100A	10.000K	170	113	
SPP12150-065A	6.500K	170	113	
SPP12150-057A	5.700K	170	113	
SPP12150-050A	5.000K	170	113	
SPP12150-040A	4.000K	159	105	
SPP12150-030A	3.000K	159	105	
SPP12150-027A	2.700K	148	99	

0.72W Colors Silver

Constant Voltage

Power 0.72W	Current 60mA	60W PS Loading 80 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPS12072-REDA	RED	36	36	
SPS12072-GREA	GREEN	35	49	
SPS12072-BLUA	BLUE	14	19	
SPS12072-YELA	YELLOW	11	15	

1.20W Gold

Constant Voltage | 3 SDCM

Power 1.20W	Current 100mA	60W PS Loading 50 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPG12120-100A	10.000K	136	113	
SPG12120-065A	6.500K	136	113	
SPG12120-057A	5.700K	136	113	
SPG12120-050A	5.000K	136	113	
SPG12120-040A	4.000K	127	106	
SPG12120-030A	3.000K	127	106	
SPG12120-027A	2.700K	118	99	

1.50W Gold

Constant Voltage | 3 SDCM

Power 1.50W	Current 125mA	60W PS Loading 40 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPG12150-100A	10.000K	170	113	
SPG12150-065A	6.500K	170	113	
SPG12150-057A	5.700K	170	113	
SPG12150-050A	5.000K	170	113	
SPG12150-040A	4.000K	159	105	
SPG12150-030A	3.000K	159	105	
SPG12150-027A	2.700K	148	99	

1.20W Chrome

Constant Current | 5 SDCM

Power 1.20W	Current 100mA	60W PS Loading 50 Total / 50 Single		
Order Code	Color	Lumen	Lm/W	
SPC12120-100A	10.000K	119	99	
SPC12120-065A	6.500K	119	99	
SPC12120-057A	5.700K	119	99	
SPC12120-050A	5.000K	119	99	
SPC12120-040A	4.000K	111	92	
SPC12120-030A	3.000K	111	92	
SPC12120-027A	2.700K	103	86	

1.50W Chrome

Constant Current | 5 SDCM

Power 1.50W	Current 125mA	60W PS Loading 40 Total / 40 Single		
Order Code	Color	Lumen	Lm/W	
SPC12150-100A	10.000K	148	99	
SPC12150-065A	6.500K	148	99	
SPC12150-057A	5.700K	148	99	
SPC12150-050A	5.000K	148	99	
SPC12150-040A	4.000K	138	92	
SPC12150-030A	3.000K	138	92	
SPC12150-027A	2.700K	129	86	

1.20W Silver

Constant Voltage | 5 SDCM

Power 1.20W	Current 100mA	60W PS Loading 50 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPS12120-100A	10.000K	119	99	
SPS12120-065A	6.500K	119	99	
SPS12120-057A	5.700K	119	99	
SPS12120-050A	5.000K	119	99	
SPS12120-040A	4.000K	111	92	
SPS12120-030A	3.000K	111	92	
SPS12120-027A	2.700K	103	86	

1.50W Silver

Constant Voltage | 5 SDCM

Power 1.50W	Current 125mA	60W PS Loading 40 Total / 25 Single		
Order Code	Color	Lumen	Lm/W	
SPS12150-100A	10.000K	148	99	
SPS12150-065A	6.500K	148	99	
SPS12150-057A	5.700K	148	99	
SPS12150-050A	5.000K	148	99	
SPS12150-040A	4.000K	138	92	
SPS12150-030A	3.000K	138	92	
SPS12150-027A	2.700K	129	86	

Luminous flux tolerance ±10% - CCT tolerance ±8%