

Anti-slip tape

Description:

Certified Anti-slip tape composed by PVC carrier coated with corundum fine mineral granules 60 grit, and acrylic solvent adhesive. Ideal solution for standard applications and suitable to many surfaces like metals, glass, ceramics, wood, marble, plastics and where there isn't a particular danger. Fairly resistance to trampling and good resistance to weathering, UV rays, oils, detergents and solvents. Available in rolls and die-cut strip form and 10 colours: Black, White, Transparent, Grey, Yellow, Brown, Blue, Red, Yellow/Black and White/Red. Apply to clean and dry surface.

TECHNICAL DATA SHEET

Adhesive:	Solvent acrylic
Carrier:	Corundum fine-grit (60 grit)
Liner:	White single sided PE coated paper
Applied weight:	860 g/m ²
Elongation:	8 %
Roll ball test (PSTC6):	1 cm
Peel adhesion (PSTC1):	13 +/- 2 N/25mm
Test DIN 51130:2014:	R13 classification
Static coefficient of friction:	Dry leather 1.01 Wet rubber 1.30
Dynamic coefficient of friction:	Dry leather 0.74 Wet rubber 1.02
Holding power:	≥ 48 hours
Impermeability:	12 months
Temperature resistance:	- 30° + 110°C
Application temperature:	Between 18°C and 35°C
Shelf life:	12 months
Outdoor age resistance:	1-3 years under average walkway conditions

Ageing in following liquid immersion:

Water or detergents:	over 72 hours
Petrol or fuel:	over 72 hours
Diesel oil:	6 hours
Brake liquid:	10 hours
Engine oil:	30 hours
Bum test: 5,5" char at 1300°C for 4 minutes, will not sustain after flame is cut off.	