

Description

Semi-transparent transfer paper with high dimension stability and high resistance to moisture. Used for the application of die-cut or computer-cut letters and symbols

Adhesive

Natural rubber, medium adhesive strength

Area of Use

The special composition of the adhesive enables problem-free transfer of die-cut or computer cut letters and symbols using both dry and wet bonding techniques. Due to its high dimensional stability, it is especially suitable for the transfer of large letters and symbols with precise positioning. This mounting paper is suitable for almost all well-known types of glossy or matt-finished films.

Technical Data

Thickness* (film with adhesive)	4.25-mil
Weight* (film and adhesive)	68#
Adhesive power (FINAT TM-1, after 20 min, stainless steel)	Adhered to stainless steel: 0.91 lb/in
Tensile strength (dry)	Along: Min. 0.36 MPa Across: Min. 0.23 MPa
Tensile strength (wet)	Along: 0.16 MPa
Elongation at break (DIN EN ISO 527)	Along: 13.5%
Shelf life**	6 months
Application temperature	> +50°F
Available lengths	300' (100-yard)
Available widths	14", 24", 30", 40", 48"

*average **in original packaging, at 68°F and at 50% relative humidity

IMPORTANT NOTICE

All ORATAPE® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORATAPE® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORATAPE® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.

All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORATAPE® is a registered trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374

techsupport-americas@orafol.com – www.orafol.com