



# Verlatex Tent FR

Soluții pentru publicitate și decor

## BRIEF DESCRIPTION

- 100% polyester fabric with 600D x 600D woven base, matte
- Super strong tensile, tear strength & water resistance feature, making it perfect as tent fabric

## FEATURES



## INK PRINTABILITY



## MATERIAL DETAILS

| Properties                     | Teste method                    | Metric                       | Imperial      |
|--------------------------------|---------------------------------|------------------------------|---------------|
| Total Weight                   | DIN EN ISO 2286-2, ASTM D751    | 270 g/sq.m                   | 7.9 oz/sq.yd  |
| Base Fabric                    | DIN 60001, ASTM D7641           | 100%polyester                | 100%polyester |
| Weave Method                   | N/A                             | Woven                        |               |
| Shrinkage                      | 210 °C, 30s                     | ≤3%                          |               |
| Flame Resistance               | DIN 4102-1-B1, NFPA 701 Test1   | IN 4102-1-B1, NFPA 701 Test1 |               |
| Recommend Fixation Temperature | N/A                             | 190°C - 210-°C, 1-2min       |               |
| Yellowing Temperature          | SUPRKC REX-C400, 30s            | ≥210°C                       |               |
| Width Available                | DIN EN ISO 3759, ASTM D751-2006 | Max 320 cm                   | 126"          |
| Standard Length                | DIN EN ISO 3759, ASTM D751-2006 | 50m                          | 55yds         |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All of the Information above shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data is available as test results and should not be used for the purpose of a lawsuit or warranty.

