



Soluții pentru publicitate și decor



Datasheet Game Changer TDS-Midi 4

Applications
Channel Letters
Lightboxes Cabinets
Cove Lighting

Operating Temperature	-30°C ~ +60°C	Lead Wire	Tin Coated Copper Wire
Storage Temperature	-30°C ~ +60°C	Lifetime TM21	>60.000 Hours
Body Material	Case: ABS Optics: Optical PC	Adhesive Tape	3M Foam
Finishing	Ultrasonic Welding	Strip Size	50 Modules/Strip

	12V / 24 DC	3 SDCM	170° BEAM ANGLE
--	-------------	--------	-----------------

PRODUCT	MIDI4			MIDI4			MIDI4		
Power	1.7W			2.4 W			2W		
Current	70mA			100mA			83mA		
Modules Per Meter	4			4			4		
60w power Supply	31 Total / 25 Single			22.5Total / 22.5 Single			27 Total / 50 Single		
Input Voltage	12V			12V			24V		
Colors	Order Code	Lumen	Lm/W	Order Code	Lumen	Lm/W	Order Code	Lumen	Lm/W
6500 K	105729	250	155	105919	300	150	105813	300	150

Can Depth ■ Optimal ■ Acceptable

Density Guideline	1"	2"	3"	4"	5"	6"	7"	8"	9"	10+"
MIDI 4 24V	■	■	■	■	■	■	■	■	■	■
MIDI 4 12V	■	■	■	■	■	■	■	■	■	■

Packaging Details	Chain	Bag	Box
	50 pcs	100 pcs	1.000 pcs

Luminous flux tolerance ±10% - CCT tolerance ±8%

