GLOSS PPF 6 MIL

Product Size and Warranty

| | | Warranty |
|-----------------|---------------|-----------|
| Gloss PPF 6 mil | 1,52 m × 15 n | n 2 years |

Technical Specifications

| - | |
|--|-------------------|
| Coating type | heat self-healing |
| Base film thickness | 125 µm |
| Gloss (Gloss PPF) | 94,2% |
| Coating | 15 µm |
| Adhesive | 25 µm |
| Adhesion (applied on steel plate, 7 days) | 8N~20N |
| Tensile Strength | 15 Mpa |
| Weather resistance test | $\Delta E < 2$ |
| Scratch resistance (brass brush, 750g, 10 times wipe) | No scratch |
| Self-healing ability | ≤5S |
| Hydrophobic | |
| Coating elongation | ≥100% |
| Elongation at break | ≥150% |
| Initial peeling force of acrylic adhesive layer (20min applied on steel plate) | ≥5N |
| Peeling force of acrylic adhesive layer/24h | ≥17,4 N |
| Anti-yellowing (1000h) | ΔE<1,8 |

Additional Information:

The above information is based solely on our current knowledge and practical experience. The information is provided without any guarantee or agreement with regards to the quality or properties of the material. This information does not constitute a warranty of any certain quality, properties and/or durability concerning our color films.

IMPORTANT NOTE

Due to the variety of applications and the ongoing development of new applications, it is up to the buyer to determine the suitability and efficiency of the product for the respective purpose of use. The buyer bears all risks arising from the use of the product. All information is subject to change.