



TRANSFER FILM FOR DTF PRINTING

TECHNICAL FEATURES

Thickness: 75 microns

Hot peel (or cold peel) with temperature range from **130°C/265°F to 160°C/320°F***

Suitable for hot melt powder glues that melt starting from 110°C/230°F (recommended actual internal oven temperature: 140°C/285°F)

Matte/matte film with **matte printing finish**

No powder residue left on the film

For brighter colors and durability, a **second press** may be needed due to temperature and application time

* The technical info depends on the DTF printer settings, the glue and inks used.

INSTRUCTIONS

PRINT ON TRANSFER FILM

Mirror design **1**

GLUE APPLICATION

Manually or with automatic shaker **2**

OVEN CURING

Internal oven temperature up to 150°C/300°F* **3**

HEAT PRESSING TRANSFER ON GARMENT

Temperature range from 130°C/265°F to 160°C/320°F* **4**

LINER REMOVAL

Hot and semi-hot, depending on temperature and application time used* **5**

STANDARD SIZES AVAILABLE

ROLLS

- h 30 cm x 100 mt / 12" x 328 ft
- h 33 cm x 100 mt / 13" x 328 ft
- h 40 cm x 100 mt / 16" x 328 ft
- h 42 cm x 100 mt / 17" x 328 ft
- h 45 cm x 100 mt / 18" x 328 ft
- h 50 cm x 100 mt / 20" x 328 ft
- h 60 cm x 100 mt / 24" x 328 ft
- h 80 cm x 100 mt / 31" x 328 ft
- h 90 cm x 100 mt / 35" x 328 ft
- h 120 cm x 100 mt / 47" x 328 ft



This product complies with Reg (CE) n. 1907/2006 (REACH)