

DATA SHEET 21135.320.35700

Folajet Canvas P

A matt top coated true canvas fabric cloth for high resolution Giclee fine art prints, classic paintings and photographs to create that traditional classic textured canvas. The coated front and the back surface are matched to a classic fine art canvas. Special inkjet coating for printing with pigment inks as well as dye inks.

Printing Systems



Rolls

Art.Number	Width (mm)	Grammage	Length (m)
21135.320.35700	610	320 g/m ²	10
21135.320.38800	914	320 g/m ²	10
21135.320.30300	1067	320 g/m ²	10
21135.320.31800	1270	320 g/m ²	10
21135.320.34800	1524	320 g/m ²	10

Technical data

Characteristic

- High brilliance of colours
- Neutral Colour image reproduction
- Suitable for dye inks
- Suitable for Latex printers
- Suitable for piezo Ink Jet printer
- Suitable for pigment inks which offers improved light stability
- Suitable for thermal Ink Jet printer
- Good ink absorption
- Excellent outstanding durability of the prints
- Excellent outstanding durability of the prints when using pigmented inks
- Instant dry

- Improved water resistance

Finish

- Brownback
- Natural, matt

Specifications

Basic weight (g)	320
Basic weight (oz)	11.29
Coating Printsides	For Ink Jet
Width (inch)	24
Width (mm)	610
Printside	Natural, matt
Length (ft)	32.81
Length (m)	10
Backside	Brown side
Base Material	Polycotton, 1:1 weave
Packing quantity	1 roll

Compatibility

- Suitable for most large format Ink Jet printers using waterbased dye, pigment or latex inks
- Not compatible with oil and solvent based systems.

Handling

- Switch off automatic cutting device (damage to print heads and cutting knives).
- Between 15-30°C and 30-70% r.h.
- Please observe the specifications for your printer and the RIP software.
- Printer mode: fine art paper, mat coated paper o.s.
- Print side = matt white side
- A preconditioning period of 24 hours within the printing environment is recommended.
- Ink Load: approx. 260 - 300% (may vary according to ink system and RIP calibration).
- Avoid fingerprints on printing side.

Storage

- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be subject to our current General Terms and Conditions.