

REFLION 3200 LED UV Roll to Roll printer is the accumulation of 15years+ technical research & development, on real industrial printers with firm body structure, purpose for most variety of outdoor application with best stability using for decades.



Features

- Grayscale printing technology, with variable drop sizes minimum from 7pl to 21pl, which ensures
 the best printing output saturated with intermediate color.
- LED UV curing system to protect the print head from direct curing light, and avoid overheating to the media by maximum lessen the curing heat.
- · Special designed for backlit printing with big ink volume printing, best for dark color printing.
- Auto carriage height adjustment from detecting the media thinkness automatically.
- Auti-static devices equipped to eliminate the bad influcence from printing.
- Printhead auto capping system to ensure the life time of the print head and isolated from the air while standby.
- Individual channel for all colors printing and white printing, best to the heads clean and ink save.
- Color + white + Color Printing & Color + White + Vanish Mode for special UV application.
- White ink recycling system to keep white printing consistency and none of blockage.
- Double negative pressure system for colors and white respectively, to keep the fluency.
- Real Industrial body of weight of 2500kgs with design of targeting long-term of stable running for years.
- User friendly with two way of media feeding in one set, to support variable kinds of media printing.

Description



Environmental friendly LED UV curing system



Dual THK linear guide



EGUS Chain



Linear motor & Metal encoder strip (optional)



Printhead anti-crash system



Electronic magnetic valve



Platform suction control



Suction control display



Infrared safeguard



Mutiple point floating media support



Strong rubber roller



Two way of media feeding in one set

Technical Specification

Print

Model REFLION 3200UV

Print Head 4~9 industrial print head

 Draft
 67sqm/h
 95sqm/h
 122sqm/h

 Production
 48sqm/h
 70sqm/h
 86sqm/h

 Quality
 35sqm/h
 50sqm/h
 62sqm/h

 Sup
 26sqm/h
 36sqm/h
 44sqm/h

Resolution Up to 635*1200dpi

Print Technology Piezoelectric inkjet, Grayscale Technology

Ink Types LED curable ink

Ink Configuration Standard CMYK, Lc, Lm, White(Optional), Vanish(Optional)

Ink cartridge size 2.5 Liter

Image process Software Aurelon , Caldera, Onyx Optional

Color management ICC based color, adjustment curves, density adjustment

Operating System Windows 8 & 10, 64bits

File format Tiff, Jpeg, Postscript, EPS, PDF, etc

Media

Support flexible media up to 330cm, with a roll diameter 40cm,

up to 360kg in weight (Vinyl, PET film, Blockout, Backlit, Synthetic

Connectivity

Interfaces USB 2.0

Curing System

LED UV lamps

Dimensions

Printer 6450mm(L)*1540mm(W)*2050mm(H)

Package 6100mm(L)*1510mm(W)*2500mm(H)

Weight

Printer 2500kgs
Package 3000kgs

Operating Conditions

Temperature 20 to 30°C

Relative Humidity 35% - 65%, non-condensing

Electricity Request

ower 5500W

Requirements Input voltage: 200 to 240 VAC, single-phase, 50/60Hz, 25A

Air

0.8 Bar

Warranty

One year limited warranty(Please contact your local dealer for details)





REFLION 3200UV

1200DPI VDS 3.2m